

PDS #5041
PRODUCT INFORMATION

valspar

1191 Wheeling Road, Wheeling, IL 60090
Phone: 847-541-9000 Fax: 847-541-7549



213447 Series Signature Colors® Eggshell Wall Paint

PRODUCT: 213447 Series

DESCRIPTION:

Valspar Signature Colors® Interior 100% Acrylic Eggshell Wall Paint.

FEATURES:

Valspar Signature Colors® offers the colors of leading designers and most popular brands in a revolutionary paint finish offering superior durability and color definition in an easy, one-coat application. A soft, low sheen finish to impart warmth to any room in your home. This durable finish resists stains and fading to maintain a washable surface and will enhance the appearance of your walls for a lifetime.

WHERE TO USE:

Ideal for use on walls, ceilings and trim. It applies easily to properly prepared and primed plaster, wallboard (drywall), wood, brick, masonry and metal.

SURFACE PREPARATION:

You must have a clean, grease-free surface. Wash walls with a mild detergent (such as TSP) and rinse well. Allow to dry thoroughly. Fill all cracks and nail holes with patching compound and spot prime. Dull glossy surfaces by sanding or by using a liquid gloss remover. Wherever indicated, use the appropriate primer to ensure best results.

TYPICAL PRODUCT PROPERTIES:
(213447)

VEHICLE TYPE: Acrylic Resin
SOLIDS: 50 % WT. 35% VOL.
VOC: 150 g/l max
WT/GAL: 11.0 lbs.
VISCOSITY: 94-100 KU
FLASHPOINT: N/A
85° GLOSS: 10-20 Units

COVERAGE:

One gallon will cover up to 400 sq. ft. (37.2 m²) on smooth surfaces. Do not thin.

FILM THICKNESS: 4.0 Mil Wet
1.4 Mil Dry

DRY TIMES:

Apply only when surface and air temperatures are 50-90°F (10-32°C). Dries to the touch in about an hour. Wait 4 hours before applying a second coat.

Jan-07

EASY APPLICATION INSTRUCTIONS:

Intermix cans of the same color to ensure color uniformity. Stir the paint before and during use. Paint the ceiling first, then the walls. Brush a 3" border around the edges. Beginning at a corner, work in 3-foot square sections. Spread the paint in a V pattern, filling in with long, even strokes in the same direction. Roll from dry area into wet to avoid lap marks. Paint the trim last. A 1-2" brush is suitable for sashes, moldings and woodwork. Wait 7 days before cleaning surface with a mild cleanser and soft sponge.

THINNING/CLEAN UP:

Do not thin. Immediately after use, wash roller covers and brushes thoroughly in warm, soapy water.

PACKAGING:

Gallons/Quarts 4 Pack

STORAGE AND DISPOSAL:

Do not freeze. Keep container closed when not in use. Do not transfer contents to other containers for storage or disposal.

Product Information Hotline:

1-888-313-5569

TYPICAL ANALYSIS (213447)

C.A.S. NO.	INGREDIENTS
7732-18-5	Water
Not Avail.	Acrylic Resin
13463-67-7	Titanium Dioxide Proprietary Inerts
14808-60-7	Crystalline Silica
1317-95-9	Crystalline Silica
107-21-1	Ethylene Glycol

CAUTIONS:

CONTAINS CRYSTALLINE SILICA

May cause eye and skin irritation. Avoid breathing spray mist or dust. If painting indoors, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness, or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. **AVOID CONTACT WITH THE EYES AND SKIN.** Wash thoroughly after use. Close container after each use. **Warning:** This product contains chemicals known to the State of California to cause cancer.

FIRST AID:

EYE CONTACT: Flush thoroughly with water for at least 15 minutes. If irritation persists, **get medical attention.** **IF INHALED:** If affected by vapor or spray mist, move to fresh air. If breathing difficulty continues, **get medical attention.** **IF SWALLOWED:** Drink 2 glasses of water. **Get medical attention immediately.**

Delayed effect from long-term exposure: Cancer Hazard. Contains crystalline silica which can cause cancer. Risk depends upon duration and level of exposure to dust generated from sanding surfaces or spray mist.

DO NOT TAKE INTERNALLY.

KEEP OUT OF REACH OF CHILDREN.

For additional safety and chronic health hazard information, refer to the Material Safety Data Sheet for this product.

EMERGENCY MEDICAL TELEPHONE:

1-888-345-5732

This product contains less than 150 g/L VOC (1.3 lb./Gal VOS)

WARNING! If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Valspar assumes no obligation or liability for use of this information. **UNLESS VALSPAR AGREES OTHERWISE IN WRITING, VALSPAR MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. VALSPAR WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.** Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option.